



ARCHIVED

Document #6

**Standard for Friction Ridge Digital Imaging
(Latent/Tenprint)**

REVISED DRAFT FOR COMMENT

1
2
3
4
5
6
7
8

1. Preamble

These standards shall be applied to the digital recording and depiction of friction ridge impressions that are to be used for examination purposes. These standards do not extend to image requirements for Automated Fingerprint Identification Systems (AFIS). Policies and procedures must be in place for the digital capture, storage, retrieval, display, and transmission of friction ridge images retained as evidence. This standard establishes requirements for the preservation of identity, authenticity, integrity, and security of friction ridge digital images. Prior to conducting digital imaging tasks in friction ridge examination cases, examiners shall have completed training appropriate to each task before them.

2. Policies

Agencies shall establish policies to determine which friction ridge digital images will be retained as evidence.

3. Image Documentation

3.1. Friction ridge digital images, documentation, or associated data shall include the following:

3.1.1. A unique case identifier. This association may be accomplished by one or more of the following methods:

3.1.1.1. As part of the digital image.

3.1.1.2. As part of the file name.

3.1.1.3. As data associated with a digital image within an imaging database.

3.1.1.4. As data associated within a standardized record (i.e., ANSI NIST, Record Level 2).

3.1.2. Date and initials or personal marking.

3.1.3. Description or identifier of the item bearing the friction ridge impression.

3.1.4. Information about the orientation or position of the friction ridge impression on the object through description, diagram(s), or photograph(s).

3.1.5. Scene location or address, if other than the laboratory.

3.1.6. Accurate scale information.

3.1.7. Make and model of the capture device.

Document #6 Standard for Friction Ridge Digital Imaging (Latent/Tenprint), REVISED DRAFT FOR COMMENT , Ver. 2.0	Date of First Issue 09/13/11	Current Issue Date 09/11/12 Web Posting Date 11/24/12
Date of Last Review N/A	Date of Next Review N/A	Appendix present/Letter No

9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33

- 34 **4. Image Quality**
- 35 **4.1.1.** Friction ridge impressions to be used for comparison purposes should be captured (color or
 36 grayscale) at a resolution no less than 1000 ppi for latent print impressions and tenprint
 37 impressions shall be captured at a resolution no less than 500 ppi when the images are sized
 38 1:1. Justification for any deviation from these recommended minima shall be documented on a
 39 case-by-case basis (e.g., the only available image was captured at less than 1000 ppi).
 40 Interpolation from a lower resolution up to a higher resolution does not meet this requirement.
 41 A list of some scanners capable of 500 or 1000 ppi resolution is available at
 42 www.fbibiospecs.org (certified product list).
- 43 **4.1.2.** In order to consistently and reliably capture images at the required resolution, digital scanners
 44 and digital cameras shall be tested in at least one configuration commonly used by the agency.
 45 It is recommended that this procedure be repeated on a regular basis, at least annually, in
 46 accordance with agency quality assurance and quality control guidelines.
- 47 **4.1.3.** If the camera is has been repaired, it is recommended the camera be re-tested prior to use. If
 48 the scanner is relocated or has been repaired, it is recommended the scanner be re-tested
 49 prior to use. Corrections shall be documented.
- 50 **4.1.4.** Details for testing 1000 ppi resolution are available in the *SWGIT Procedure for Testing*
 51 *Scanner Resolution for Latent Print Imaging* and the *Procedure for Testing Digital Camera*
 52 *System Resolution for Latent Print Photography documents* [2] [3]. Because of the variables
 53 involved in friction ridge digital imaging, it may be impractical to do this level of testing using all
 54 scanner and camera, lens, and filter configurations/settings.
- 55 **4.2.** Grayscale digital imaging shall be at a minimum of 8 bits. Color digital imaging shall be at a minimum of
 56 24 bits.
- 57 **4.3.** Friction ridge impression digital images to be used for comparison purposes shall be stored and
 58 transmitted without compression or with lossless compression. Capture in a raw file format is
 59 recommended.
- 60 **5. Image Integrity**
- 61 **5.1.** A primary image is the result of the first recording of an image onto media. An original image is an
 62 accurate replica (bit-for-bit value) of the primary image. Each original image shall be stored in a manner
 63 that permits authentication.
- 64 **5.2.** Enhancement shall only be conducted on working copies of the original image. Working copies used in
 65 forensic case examination shall be saved as a separate copy and shall not replace the original image.
- 66 **5.3.** Digital images captured from lifts or from conventional photographs or negatives shall not replace the
 67 lift, negative, or photograph as original images.
- 68 **5.4.** Agencies shall have procedures to ensure the accessibility of digital images: images may be archived in
 69 a format to ensure their accessibility and hardware and software may be archived to ensure
 70 accessibility of images [1].
- 71 **6. Casework Documentation**
- 72 **6.1.** Procedures shall be in place to ensure the accuracy and completeness of documentation.
- 73 **6.2.** Casework documentation shall distinguish friction ridge impression digital images from lifts or
 74 photographs.
- 75 **6.3.** The application of digital image processing (enhancement) techniques shall be documented. This
 76 documentation shall be sufficient to enable evaluation or replication of the digital image processing
 77 techniques.
- 78

Document #6 Standard for Friction Ridge Digital Imaging (Latent/Tenprint), REVISED DRAFT FOR COMMENT , Ver. 2.0	Date of First Issue 09/13/11	Current Issue Date 09/11/12 Web Posting Date 11/24/12
Date of Last Review N/A	Date of Next Review N/A	Appendix present/Letter No

79 **7. References**

80 [1] SWGIT, *Best Practices for Archiving Digital and Multimedia Evidence (DME) in the Criminal Justice*
81 *System*, 6/4/07, ver. 1.0, www.theiai.org/guidelines/swgit/guidelines/section_15_v1-0.pdf.

82 [2] SWGIT, Section 21, Procedure for Testing Scanner Resolution for Latent Print Imaging, ver. 1.0
83 2012.01.12, http://theiai.org/guidelines/swgit/guidelines/section_21_v1.pdf

84 [3] SWGIT, Section 22, Procedure for Testing Digital Camera System Resolution for Latent Print
85 Photography, ver. 1.0 2012.01.13, [ttp://theiai.org/guidelines/swgit/guidelines/section_22_v1.pdf](http://theiai.org/guidelines/swgit/guidelines/section_22_v1.pdf)

86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114

Document #6 Standard for Friction Ridge Digital Imaging (Latent/Tenprint), REVISED DRAFT FOR COMMENT , Ver. 2.0	Date of First Issue 09/13/11	Current Issue Date 09/11/12 Web Posting Date 11/24/12
Date of Last Review N/A	Date of Next Review N/A	Appendix present/Letter No

115 **8. Revision Table**

Version	Effective Start	Effective End	Posted	Archived	Change
1.0	08/08/01	12/23/08	08/08/01	12/23/08	Original Issue
1.0 Draft For Comment	N/A	N/A	09/12/08	N/A	
1.0	12/23/08	09/14/09	12/23/08	12/21/09	Major rewrite
1.1 Draft For Comment	N/A	N/A	04/21/12	N/A	1. Updated Section 3.1 2. Added Sections 3.1.1, 3.1.2, 3.1.3
2.0 Revised Draft For Comment	N/A	N/A	11/24/12	N/A	1. Revised numbering 2. Preamble, Sections 3.1, 3.1.1, 3.1.2, 3.1.3 modified Reformatted (start of new version number)

116
117
118

Document #6 Standard for Friction Ridge Digital Imaging (Latent/Tenprint), REVISED DRAFT FOR COMMENT , Ver. 2.0	Date of First Issue 09/13/11	Current Issue Date 09/11/12 Web Posting Date 11/24/12
Date of Last Review N/A	Date of Next Review N/A	Appendix present/Letter No